



ThermaCells™

Insulating Ceramic Additive for paint

DIRECTIONS FOR USE

The additive should be gradually stirred into the appropriate size container of paint.

One Pre-measured 1 gallon package of Ceramic Additive for one gallon of paint or a Pre-measured 5 gallon package of Ceramic Additive for a 5 gallon pail of paint.
(Mixing ratio is 4 parts paint to 1 part Ceramic Additive)

If you purchased a bulk contractor package, simply measure out a 1 qt container (32 oz. vol.) or use a kitchen measuring cup (4 cups = 1 QT of Additive for each one gallon of paint).

DO NOT try to mix this package directly into your container of paint as it will not all fit. Get a second or larger container to use for mixing purposes. Simply pour your paint into the larger sized container and mix in the Ceramic Additive while stirring slowly to avoid clumping of the additive. Make sure to completely mix all of the Ceramic Additive into your paint! Always stir your paint for a minute or two prior to commencing painting if the paint has been sitting for more than 2 hours since last used.

Note: Recommended Roller Size 1/2" to 3/4" nap depending on surface texture..
Spraying: Remove all filters Tip Size .019 - .024 or larger depending on viscosity of paint.

The Ceramic Additive will leave a mild texture (suede look) to the surface to which it has been applied which will help hide defects in a wall surface.

We require 2 coats of paint containing the insulating ceramics to insure complete, uniform distribution of the insulating "beads."

NOTE: If needed add up to 1 pint of water per gallon of paint or reduce with Hy-Tech Acri-Flow to help the paint to flow better!

SAFETY DATA: Hy-Tech Ceramic Additive is a very environmentally friendly blend of organic ceramic microspheres which are non-toxic. Inhalation of large amounts of this product in its free powdered state could cause respiratory irritation and a dust mask should be worn if working around large airborne concentrations of this product prior to mixing with paint. If eye irritation occurs, flush eyes with water and if problems persist consult a physician.

*Hy-Tech
159 Parkhill Blvd.
Melbourne, FL 32904
www.hytechsales.com
PH Toll Free 1-866-649-8324*

Hy-Tech ThermaCels™ Ceramic Paint Additive

Materials Safety Data Sheet

Identification of product:

Product name - Hy-Tech ThermaCels™ Ceramic Microspheres
Manufacturer - Hy-Tech Thermal Solutions, LLC.
Address - 159 Parkhill Blvd., W. Melbourne, FL 32904
Telephone Number - 321-984-9777
Sales Name - Hy-Tech Insulating Paint Additive

This product contains ingredients considered to be trade secrets by Hy-Tech Thermal Solutions, LLC.

This MSDS does, however, disclose all necessary information needed to handle and use the product safely.

TSCA and Other Chemical Name: Clay Mixture (CAS 66402-68-4)

Inventories The Chemical Abstract Services (CAS) number for Hy-Tech paint additive is 66402-68-4, which is listed on the TSCA (U.S.), CDSL (Canada), EINECS (E.U.), AICS (Australia), KECI (Korea) and PICCS (Philippines) inventories. Because of their physical characteristics, the additive can be considered articles according to above listed inventories, and therefore exempt from chemical registration requirements.

DOT Hazard Class -Not Applicable DOT Shipping Name -Non-regulated article

The NAFTA Harmonized Tariff Code is 6815-99-4000.

Chemical and physical data:

Appearance & Odor -Dry white powder, odorless

Ingredients-Mixture Ceramic Spheres

Fire, Explosion and Reactivity Hazard Data:

Flash Point (° F) -Noncombustible

Special Fire Fighting Procedures -Not Applicable

Stability -Stable Conditions to Avoid - None known

Incompatibility (materials to avoid) - None Known

Hazardous Decomposition Products -None

Spills and Disposal: Environmental Hazard -None Known.

Spillage -Sweep, scoop, or vacuum material

Waste Disposal Method -Landfill according to local, state and federal regulations.

Disposed material is not a RCRA hazardous waste.

Health Hazard Data:

Eye Contact - Causes irritation. Skin Contact -May cause dehydration and irritation

Inhalation -Causes irritation to respiratory tract

Chronic Hazards -No known chronic hazards. Not listed by OSHA, NTP or IARC as a carcinogen. Medical conditions aggravated by exposure -Asthma and lung diseases

First aid procedures - In case of contact immediately flush eyes with plenty of water.

Get medical attention if irritation persists. If inhaled, remove to fresh air

Special Protection Information:

Respiratory protection -Use NIOSH-certified dust respirator where dust occurs.

Observe OSHA regulations for respirator use (29 CFR 1910.134)

Gloves -Cotton gloves are usually sufficient to protect hands from irritation arising from handling this product

Eye protection -Chemical goggles

Personal hygiene -Avoid breathing dust. Wash thoroughly after handling

Engineering control - Use with adequate ventilation

This product does not contain crystalline silica and is not listed on any of the following regulatory lists: EPCRA, CERCLA, CA PROP 65, and US or specific state OSHA hazardous chemicals