



"A NASA Technology Spinoff Company"

SR#1220 Bond-It

Clear, Acrylic Bonding Agent



Hy-Tech Thermal Solutions, LLC www.hytechsales.com
Headquarters: 159 Park Hill Blvd., W. Melbourne, FL 32904 USA Phone (321) 984-9777, Fax (321) 984-1022

Description:

Bond-It is an exterior/interior, clear, acrylic sealer and bonding coat. It can be used on a variety of surfaces, such as plaster, masonry, roof shingles and other roofing materials to ensure an appropriate adhesion of top coatings.

As a primer, **Bond-It** provides an adhesive like surface which aids in the bonding of top-coat finish paints to the surface. **Bond-It** is fast drying and results in a medium, low sheen.

Bond-It is recommended for use with Hy-Tech's protective, insulating roof coatings. For more information on **Roof Guard**, **Insul Cool Coat**, **Bus Kote**, and **Perma-Kote Plus**, please visit our website at www.hytechsales.com

Benefits:

- Gives the surface the exceptional ability to bond with other top-coatings
- Fast drying
- Comes as a milky white, but dries clear
- Easy cleans up; cleans with soap and water
- Contains no harmful solvents; water-based so it is non-toxic, easy to use, and environmentally friendly!

Surface Preparation:

Be sure the surface is clean, dry, and free from dirt, grease, wax, or other contaminants. Glossy surfaces should be dulled by sanding. All surface defects such as peeling, cracks and patches should be corrected before application. Previously painted surfaces should be washed with a power washer to remove all chalk and loose paint. Rusted metal should be treated with rust converter and then primed with Hy-Tech's **#18 Metal Prime**

Application:

Stir thoroughly before use. Do not thin! Apply one coat of **Bond-It** to the prepared surface. Allow 2-3 hours of drying before top-coating.

May be applied by brush, roller, conventional spray or airless spray.

Bond-It covers approximately 150-250 square feet per gallon, depending on the porosity of the surface.

For a smooth surface, the estimated coverage is 200-250 square feet per gallon.

For a rough surface, the coverage is roughly 150-200 square feet per gallon.

KEEP FROM FREEZING
Do not apply when temperatures are below 50°F. Coatings should only be applied when ventilation is adequate.

CAUTION! KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Hy-Tech Thermal Solutions, LLC nor our agents shall be responsible for the use or results of use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of the product for each specific project and for the health and safety of personnel working in the area. For information on safety hazards associated with this product please refer to MSDS sheets.