



Encapsulguard Encapsulating Coating



Hy-Tech Thermal Solutions, LLC www.hytechsales.com
 Headquarters: 159 Park Hill Blvd, W. Melbourne, FL 32904 USA Phone (321) 984-9777, Fax (321) 984-1022

<p>Description:</p> <p>Encapsulguard is a high-quality, 100% acrylic, elastomeric water-based coating, that will provide an economical, effective and safe sealing of lead base paints and asbestos materials. Encapsulguard provides long-term protection over a wide variety of surfaces such as stucco, wood, concrete, brick, metal, ceilings, roofing materials, etc. Encapsulguard is non-toxic, mildew-resistant and UV resistant. It has excellent flexibility, will provide insulation and water resistance. Encapsulguard is cost-effective and is designed for both interior and exterior use.</p>	<p>Why use <u>Encapsulguard</u>?</p> <p>In order to remove the old materials that contain lead or asbestos, "hazardous material" abatement companies need to be called. These companies are the only ones permitted to remove the old hazardous materials--but at great expense. Since local waste disposal sites do not accept hazardous materials, those hazardous materials need to be hauled to a designated hazardous waste site at great expense. By using Encapsulguard, there is no need to remove the old, existing materials and no need to remove any mechanical equipment that can cause ruptures in the system and cause asbestos and lead dust to be air-born.</p> <p style="text-align: center;">KEEP FROM FREEZING</p> <p style="text-align: center;">Do not apply when temperatures are below 50°F. Coatings should only be applied when ventilation is adequate.</p>	<p>Application:</p> <p>Encapsulguard has been specially formulated to be applied directly over asbestos-based and lead base painted surfaces. NO PRIMER NEEDED!!! It has great adhesion and will adhere to galvanized metal, metal, glass, tiles, wood, stucco, concrete, brick, linoleum, ceilings, interior walls and other surfaces.</p> <p>Encapsulguard is ready to use and requires no thinning, dilution, or additions. May be tinted locally, light to mid-range colors. Easily applied by brush, roller or spray</p> <p>Encapsulguard covers approximately 150 square feet per gallon</p> <p>Drying Time:</p> <p>Allow 12 hours minimum between coats.</p>
---	---	---

**CAUTION! KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.**

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Hy-Tech Thermal Solutions, LLC nor our agents shall be responsible for the use or results of use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of the product for each specific project and for the health and safety of personnel working in the area. For information on safety hazards associated with this product please refer to MSDS sheets.