



Insulating Primer #14



Hy-Tech Thermal Solutions, LLC www.hytechsales.com
 Headquarters: 159 Park Hill Blvd., West Melbourne, FL 32904 USA Phone (321) 984-9777, Fax (321) 984-1022

<p>Description:</p> <p>Insulating Primer #14 is a high quality, white pigmented latex primer/sealer, fortified with Hy-Tech Thermal Solutions' ThermaCels™, which provide insulation and sound reduction, along with a uniform, easy to apply flat priming finish. It has been formulated for use on nearly all interior and exterior surfaces. It may be topcoated with most conventional latex or alkyd based products, but is designed for use as a system with other Hy-Tech fine finishes. Insulating Primer #14 is a water-reducible, alkali resistant primer ideally suited for sealing drywall without raising the paper fiber. Insulating Primer #14 offers fast drying, low odor, and may be used under all sheens (flat, eggshell, satin, semi and high gloss).</p> <p>Insulating Primer #14 covers roughly 250-400 square feet per gallon.</p>	<p>Benefits:</p> <ul style="list-style-type: none"> • Fast drying • Insulates! • Environmentally friendly and non-toxic • Easily cleaned with soap and water • The small texture helps to hide minor surface defects such as drywall joints, dings and dents. • May be topcoated with a variety of coatings, but mainly for use with other Hy-Tech finish coats • Can be applied by brush, roller or spray. <p style="text-align: center;">KEEP FROM FREEZING Do not apply when temperatures are below 50°F. Coatings should only be applied when ventilation is adequate.</p>	<p>Surface Preparation:</p> <p>Surface must be dry, free of wax, grease, oil and other foreign material.</p> <p>Application:</p> <p>Stir using a vigorous, lifting motion or shake thoroughly before using. Apply with brush, roller, conventional or airless spray equipment.</p> <p>Spray application: Remove all filters and use a .019-.021 tip.</p> <p>Drying Time: Dries dust free in 1 hour. May be recoated after 4 hours.</p> <p>Thinning: Formulated for use at package consistency. For application with spray equipment, some thinning may be required. <i>Use only clean water and do not exceed 1 pint of water per gallon</i></p> <p>Coverage: 250-300 sqft per gallon</p>
--	---	---

**CAUTION! KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.**

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Hy-Tech Thermal Solutions, LLC nor our agents shall be responsible for the use or results of use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of the product for each specific project and for the health and safety of personnel working in the area. For information on safety hazards associated with this product please refer to MSDS sheets.