



Stain Blocker

Product group - Primers



Hy-Tech Thermal Solutions, LLC www.hytechsales.com
Headquarters: 159 Parkhill Blvd, W. Melbourne, FL 32904 USA Phone (321) 984-9777, Fax (321) 984-1022

<p>DESCRIPTION:</p> <p>Stain Blocker is a fast-drying white-pigmented acrylic latex undercoat. It is formulated for use on all types of exterior and interior surfaces - previously painted or new work. Any oil or latex finish paint can be applied over it.</p> <p>Stain Blocker's breathable film lets interior house moisture escape, minimizing exterior paint blistering and peeling. Flaking and cracking on soft, dimensionally unstable wood is less likely too, because Stain Blocker flexes with the wood as it expands and contracts with temperature changes. Stain Blocker adheres to chalky weathered siding and to glossy trim without sanding. It's ideal for repainting vinyl or aluminum siding, brick, masonry, new wood or old weathered paints.</p> <p>Stain Blocker bonds to tough surfaces like formica, enamel painted metals, varnished wood, paneling and to old high gloss paints. Stain Blocker makes interior painting an easy job.</p>	<p>FEATURES</p> <p>Interior and exterior Great adhesion without sanding Seals stains, graffiti and tannin bleed Dries in 1 hour Easy soap & water clean up</p> <p>Chemical & Weather Resistant: Stain Blocker is resistant to common industrial chemicals, acid rain and other VOC compounds</p> <p>SURFACE PREPARATION All substrates to be coated must be pressure washed clean, dry and sound. Loose, flaking or powdery rust, dirt, gravel and other surface contaminants not removed with power washing must be completely removed before priming. The surface MUST BE CLEAN</p> <p>PROPERTIES</p> <ul style="list-style-type: none"> • Appearance: Satin Finish • Color: White, Tintable • Vehicle Type: Acrylic Copolymer Emulsion • Solids by Volume: 33.84% • Solids by Weight: 48.36% • Weight per Gallon: 10.7 lbs./gal. • Maximum VOC Content: 450 grams/liter • Spread Rate: 400-450 ft²/gal. • Cure Time: To Touch: 2-4 hours - Recoat: 8 hour • Thinner: WATER • Packaged: 1 and 5 gallon containers. 	<p>APPLICATION</p> <p>Apply by brush, roll or airless spray. If rolling, apply the paint generously, making sure to work the paint into all cracks and voids.</p> <p>Airless Spray Tip Size: Can vary between .017 - .024". Recommended tip is #619 Airless hose: 1/4" or 3/8" I.D.</p> <p>CLEAN UP Clean up all tools and equipment, promptly, with warm soapy water. Dried product can be removed with Xylene or Xylol</p> <p>DRYING TIME At 77°F an 50% relative humidity: To Touch: 2 - 4 hours To Recoat: 6 - 12 hours. This will vary depending on weather and application conditions.</p> <p>SPECIAL INFORMATION Do not allow to freeze or store in prolonged sunlight. Do not apply when surface temperature is below 50°F or ambient temperature is above 90°F. Do not apply if rain is predicted within 48 hours.</p>
---	--	--

CAUTION! KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Hy-Tech Thermal Solutions, LLC nor our agents shall be responsible for the use or results of use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of the product for each specific project and for the health and safety of personnel working in the area. For information on safety hazards associated with this product please refer to MSDS sheets.