



## Super Seal Clear Acrylic Sealer



Hy-Tech Thermal Solutions, LLC    www.hytechsales.com  
 Headquarters: 159 Parkhill Blvd, W. Melbourne, FL 32904 USA Phone (321) 984-9777, Fax (321) 984-1022

<p><b>Description:</b></p> <p><b>Super Seal</b> is a clear, gloss, interior/exterior waterproof sealer and finish. Designed to effectively bond to non-porous surfaces, <b>Super Seal</b> will preserve, seal and protect the surface, while providing superior protection from moisture penetration on hard-to-stick-to surfaces. Enriched with special additives, <b>Super Seal</b> will form a beautiful, non-yellowing, clear gloss finish that reduces the growth of mold and mildew on most any surface. Reduces harmful water intrusion of the surface by sealing most cracks, crevices and pores to create a sheeting off of water.</p> <p><b>Super Seal</b> is ideal for most surfaces, including: roof tiles, wood, aluminum, steel, galvanized, tin, masonry, brick and stone, cement tile and grout, Plexiglass and acrylic skylights, polyacrylate sunrooms and conservatories and most all other surfaces.</p>	<p><b>Benefits:</b></p> <ul style="list-style-type: none"> <li>• Easy Clean up!</li> <li>• Will adhere to a variety of hard-to-bond-to surfaces</li> <li>• Environmentally friendly and non-toxic</li> <li>• Will provide protection from moisture</li> <li>• Resists the growth of mold and mildew</li> <li>• Can be applied by brush, roller or spray</li> </ul> <p>With the addition of Hy-Tech ThermaCels™ ceramic additive you can also provide an insulating barrier to heat penetration!</p> <p>The addition of ThermaCels however, will make the coating opaque and resemble frosted glass. This is due to the color of the ceramic particles themselves.</p>	<p><b>Application:</b></p> <p>It is essential that the surface be cleaned well with a chlorine and water solution removing all dirt, mildew, stains and other contaminants. <b>Super Seal</b> will resist mildew growth but will not kill mildew already on the surface. Apply straight from the can, do not thin. Apply at temperatures above 50 degrees F. Do not apply if rain or heavy dew is expected within 3 hours. Apply by brush, roller or spray, <b>DO NOT</b> allow puddling. Two coats are recommended with 4 hours dry time between coats. Spread rates will vary between 150-300 square feet per gallon.</p> <p style="text-align: center;"><b>KEEP FROM FREEZING</b>      Do not apply when temperatures are below 50°F.      Coatings should only be applied when ventilation is adequate.</p>
--	---	---

**CAUTION! KEEP OUT OF REACH OF CHILDREN.**

**DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.**

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Hy-Tech Thermal Solutions, LLC nor our agents shall be responsible for the use or results of use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of the product for each specific project and for the health and safety of personnel working in the area. For information on safety hazards associated with this product please refer to MSDS sheets.